


* R varies between 0 to 6 (152)


CROSS SECTION

ELEVATION

CASE I, (H+T-R) < 18 (457), TOP MOUNT



TOP VIEW



SOCKET ASSEMBLY FOR CASE I

WEAK POST GUARDRAIL ATTACHED TO CULVERT


(Sheet 2 of 6)

STANDARD 630111-01

PASSED January 1. 2020
ENGINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2020

ENGINEER OF DESIGN AND PROVIRONMENT




 st R varies between 0 to 6 (152)

CROSS SECTION

ELEVATION

CASE II, (H+T-R) < 18 (457), SIDE-MOUNT THROUGH-BOLT




* R varies between 0 to 6 (152)


CROSS SECTION

ELEVATION

CASE III, (H+T-R) < 18 (457), SIDE-MOUNT ANCHORED



TOP VIEW





SOCKET ASSEMBLY FOR CASES II & III

WEAK POST GUARDRAIL ATTACHED TO CULVERT

(Sheet 3 of 6)


STANDARD 630111-01






Illinois Department of Transportation

CASE IV, $(H+T-R) \ge 18 (457)$, TOP MOUNT



TOP VIEW




SIDE VIEW FRONT VIEW

SOCKET ASSEMBLY
FOR CASE IV

WEAK POST GUARDRAIL ATTACHED TO CULVERT

(Sheet 4 of 6)


STANDARD 630111-01



CROSS SECTION

ELEVATION


CASE V, $(H+T-R) \ge 18 (457)$, SIDE-MOUNT, THROUGH-BOLT




CROSS SECTION

ELEVATION

CASE VI, (H+T-R) ≥ 18 (457), SIDE-MOUNT ANCHORED



TOP VIEW



SIDE VIEW

FRONT VIEW

SOCKET ASSEMBLY FOR CASES V & VI

WEAK POST GUARDRAIL ATTACHED TO CULVERT

(Sheet 5 of 6)

STANDARD 630111-01

PASSED January 1, 2020 SUBSINEER OF POLICY AND PROCEDURES

APPROVED January 1, 2020 17-17

