



## THRIE-BEAM BULLNOSE NOSE CABLE



RCM02

SHEET NO.

DATE:

1 of 2

9/13/2013

### **SPECIFICATIONS**

The thrie-beam bullnose nose cable shall use “Cold Tuff” Button, S-409 Size No. 12, SB 2 7/8” [73], Stock No. 1040395 for 5/8” [16] D (6x25) wire rope (or any similarly sized swage-grip button ferrules).

The wire rope shall be 5/8” [16] diameter 6x19 wire strand core or independent wire rope core (IWRC), zinc-coated, right regular lay wire rope conforming to AASHTO M30.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

### **INTENDED USE**

The thrie-beam bullnose nose cable is intended for use in SET03a-b.

### **CONTACT INFORMATION**

Midwest Roadside Safety Facility  
Nebraska Transportation Center  
University of Nebraska-Lincoln  
130 Whittier Research Center  
2200 Vine Street  
Lincoln, NE 68583-0853  
(402) 472-0965  
Email: [mwrsf@unl.edu](mailto:mwrsf@unl.edu)  
Website: <http://mwrsf.unl.edu>

### **THRIE-BEAM BULLNOSE NOSE CABLE**

**RCM02**

SHEET NO.

DATE:

2 of 2

9/13/2013

