



BCT TIMBER POST FOR THRIE-BEAM BULLNOSE END TERMINAL



PDF04

SHEET NO.

DATE:

1 of 2

10/22/2008

SPECIFICATIONS

Posts shall be made of timber with a stress grade of at least 1200 psi [8 MPa]. Grading shall be in accordance with the rules of the West Coast Lumber Inspection Bureau, Southern Pine Inspection Bureau or other appropriate timber association. Minimum of SYP Grade No.1 or better. Timber for posts shall be rough-sawn (unplaned) or S4S (surfaced four sides) with finished dimensions indicated. The tolerances shown are applicable to the finished post since the post must slide inside foundation tube PTE06. The post edges may require beveling below the 7/8" [22] hole to allow the post to fit into the steel foundation tube.

All timber shall receive a preservation treatment in accordance with AASHTO M-133 after all end cuts are made and holes are drilled. Cross-sectional properties shown below are based on the finished dimensions and are calculated through the 2 1/2" [64] weakening hole.

DESIGNATOR	AREA in. ² [10 ³ mm ²]	I _x in. ⁴ [10 ⁶ mm ⁴]	I _y in. ⁴ [10 ⁶ mm ⁴]	S _x in. ³ [10 ³ mm ³]	S _y in. ³ [10 ³ mm ³]
PDF04	27.5 [18]	186 [78]	69 [29]	50 [810]	25 [413]

Dimensions tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

This timber post is a component of the Thrie-Beam Bullnose End Terminal (SET03). This post is connected to a steel foundation tube (PTE06) using a FBX16a bolt and nut and FWC16a washers. The anchor cable assembly in system SET03 connects to the post through the 2 1/2" [64] hole at the base. Post sleeve (FMM02) should be inserted into the 2 1/2" [64] hole at the base of the post.

CONTACT INFORMATION

Midwest Roadside Safety Facility
E527 Nebraska Hall
Lincoln, NE 68588-0529
(402) 472-0965
Email: mwrsf@unl.edu
Website: <http://mwrsf.unl.edu/>



BCT TIMBER POST FOR THRIE-BEAM BULLNOSE END TERMINAL

PDF04

SHEET NO.

DATE:

2 of 2

10/22/2008

