



ELEVATION VIEW



PROFILE VIEW



PERPENDICULAR TO SLOTS

NOSE CABLE ANCHOR PLATE



FPA04

SHEET NO.

1 of 2

DATE:

9/12/2013

SPECIFICATIONS

The nose cable anchor plate shall be formed from ASTM A36 steel plate and zinc-coated according to AASHTO M111 (ASTM 123) except when corrosion resistant steel is requested. No punching, drilling or cutting is permitted after the anchor plate is zinc coated. When corrosion resistant steel is desired, the bracket shall not be painted or zinc-coated.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

INTENDED USE

The nose cable anchor plate is used in SET03a-b, three-beam bullnose end terminal.

CONTACT INFORMATION

Midwest Roadside Safety Facility
Nebraska Transportation Center
University of Nebraska-Lincoln
130 Whittier Research Center
2200 Vine Street
Lincoln, NE 68583-0853
(402) 472-0965
Email: mwrfsf@unl.edu
Website: <http://mwrfsf.unl.edu>

NOSE CABLE ANCHOR PLATE

FPA04

SHEET NO.

DATE:

2 of 2

9/12/2013

