



PLAN VIEW



ELEVATION VIEW



PROFILE VIEW

## FOUNDATION TUBE FOR BULLNOSE END TERMINAL SLIP POST



PTE08

SHEET NO.

1 of 3

DATE:

10/11/2013

## SPECIFICATIONS

The foundation tubes shall be manufactured using ASTM A500 Grade B steel. The section shall be manufactured such that it conforms to the geometry of ASTM A500 Grade B for TS-8x6x3/16" [TS-203x152x4.8].

The foundation tube top plate shall be made from ASTM A36 steel.

After the section is cut, all holes are drilled or punched, and welds completed, the component should be zinc-coated according to AASHTO M111 (ASTM A123) unless corrosion resistant steel is used. When corrosion resistant steel is used, the foundation tube shall be zinc-coated according to AASHTO M111 (ASTM A123) and the portion above the soil shall not be zinc-coated, painted, or otherwise treated.

Dimensional tolerances not shown or implied are intended to be those consistent with the proper functioning of the part, including its appearance and accepted manufacturing practices.

## INTENDED USE

The foundation tube for bullnose end terminal post is a component of the Thrie-Beam Bullnose End Terminal (SET03a-b) guardrail system.

## CONTACT INFORMATION

Midwest Roadside Safety Facility  
Nebraska Transportation Center  
University of Nebraska-Lincoln  
130 Whittier Research Center  
2200 Vine Street  
Lincoln, NE 68583-0853  
(402) 472-0965  
Email: [mwrslf@unl.edu](mailto:mwrslf@unl.edu)  
Website: <http://mwrslf.unl.edu>

## FOUNDATION TUBE FOR BULLNOSE END TERMINAL SLIP POST

**PTE08**




SHEET NO.

DATE:



2 of 3

10/11/2013





FOUNDATION TUBE



FOUNDATION TUBE TOP PLATE

## FOUNDATION TUBE FOR BULLNOSE END TERMINAL SLIP POST



PTE08

SHEET NO.

DATE:

3 of 3

10/11/2013