



### Portable Rigid Panel System

- \* Vertical Upright Mast - 44.45 mm x 44.45 mm x 2.63 mm wall x 2740 long telespar galvanized steel tubing
- \* Legs, Horizontal Portion - 50.80 mm x 50.80 mm x 4.68 mm thicknesses x 1222 mm long L-shaped steel angle
- \* Legs, Vertical Stub - 50.80 mm x 50.80 mm x 2.64 mm wall x 151 mm long steel tubing
- \* All telespar steel tubing contain 9.53 mm diameter punched holes, spaced 25.40 mm on center, along the total length
- \* Vertical stub of the leg is tack welded to horizontal portion of the leg on three sides
- \* Masts slide inside vertical stub of legs - No bolt or fastening device used
- \* Panel - Reflective plywood, 1218 mm wide x 1219 mm long with a 15.88 mm thickness
- \* Secondary Panel - Reflective plywood, 609 mm wide x 610 mm long with a 15.88 mm thickness
- \* Panels fastened to vertical mast supports with 9.5 mm x 76 mm 16-hex bolt with 14.3 mm nut and 38.1 mm flat washer
- \* Light - "Work Safe Supply" Type A Flashing Warning Light attached to the sign panel
- \* Ballast - 31.75-kg of sandbags at end of each leg