Issue No. I

2006

JANUARY

ISSUE FEATURE:

Midwest Guardrail System

INSIDE THIS ISSUE:

Midwest Guardrail System	I
MGS at 7:1 Flare Rate	2
MGS Behind 6 in. Curb	2
MGS Perform- ance Summary	3
MGS Thrie-Beam Transition	3
MGS with I/4 Post Spacing	3
Ongoing MGS Testing	3
Questions and Answers	4
Recent Research Reports	4
Ongoing Research	4

The Midwest Guardrail System

Koadside Keview

Midwest Roadside Safety Facility, University of Nebraska-Lincoln



The Midwest Guardrail System (MGS) is a nonproprietary, modified W-beam guardrail system that was specifically designed for the high center of gravity vehicles found on today's roadways.

The system, developed with funding from participating states of the Midwest Pooled Fund Program, is completely generic with no patented parts, meets the NCHRP Report 350 TL-3 requirements and uses standard W-beam with a higher rail mounting height, a shallower post embedment depth, deeper blockouts, and a modified post placement scheme as compared to previous guardrail systems which have often failed to perform adequately for the larger and higher vehicles.

The standard MGS has been tested with the top of the rail as high as 32 in. and has been approved for use with a 27 5/8 in. mounting height. The taller mounting height allows for a typical 3 in. overlay without any adjustments or modifications to the guardrail.

MGS is also the first system to successfully meet the NCHRP Report 350 requirements when placed behind a 6 in. curb, and it has been successfully tested with flare

Specifics:

- 31 in. Nominal Top Rail Mounting Height
- 12 in. Blockouts
- 40 in. Embedment Depth
- Mid-Span Rail Splices
- Standard Steel or Wood 6 ft Posts
- Standard 12-Gauge W-Beam
- Non-Proprietary

Midwest Guardrail System isometric view.

rates as steep as 7:1.

An asymmetrical W-beam to thrie-beam transition has been developed for the system allowing for the connection to most thrie-beam bridge transitions. This development represents the first asymmetrical W-beam to thrie-beam transition to meet the NCHRP Report 350 requirements.

For locations where a reduced barrier deflection is required, the system has been approved with both halfand quarter-post spacing.

In addition, MGS has been successfully tested with the proposed NCHRP 350 update vehicles which are larger than the current vehicles.

To complete the package, the system has been tested successfully with three proprietary end terminals, both tangent and flared systems.

The Midwest Guardrail System has been fully reported in TRR Paper Nos. 02-3157, Development of the Midwest Guardrail System, and 04-4778, Midwest Guardrail System for Standard and Special Applications. It was also reported in the MwRSF research report no. TRP-03-139-04.



MGS full-scale crash testing with 2270P and 1100C, the proposed NCHRP 350 update vehicles.

MGS reports, papers, and drawings can be found at www.mwrsf.unl.edu 🔮



PAGE 2



8"



Thrie-Beam Transition

MGS Performance Summary

Pine, and

posts.

I

١

Douglas Fir

System Test (Ho) (Ho) 32 in Height 310 117 403 343 32 in Height 310 117 403 343 32 in Height 310 117 403 343 12 Pass Spacing Simulation 23.8 33.1 12 Pass Spacing Simulation 23.3 33.0 11.2 12 Pass Spacing Simulation 23.3 33.0 11.2 12 Pass Spacing Simulation 33.1 71.8 84.3 21.4 12 Pass Spacing Simulation 33.1 71.8 84.3 21.4 12 Pass Spacing Simulation 33.1 71.8 84.3 21.4 12 Pass Spacing Simulation 31.1 71.8 84.3 21.4 12 Pass Spacing Simulation 31.1 71.8 84.3 21.4 12 Pass Spacing Simulation Simulation 92.4 93.1 94.3 94.3 12 Pass Spacing Simulation Simulation Simulation 94.3 94.3 94.3 94.3 94.3 </th <th></th> <th></th> <th>[</th> <th>Deflection</th> <th>Working Width</th>			[Deflection	Working Width
Silindard (1 m.) 3:10 17.4 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:30 4:31 4:		System	Test	(in.)	(in.)
A the basis of		Standard (31 in.)	3-11	43.1	49.6
11 these spacing 11 these space		oz III. ⊓eigni 6 in. Curb	3-10	17.4	40.3
12 Persbasent sinuation 278 131 17 Flave Rate 311 278 307 17 Flave Rate 311 278 307 17 Flave Rate 311 278 201 17 Flave Rate 311 278 201 11 42 214		1/4 Post Spacing	3-11	40.3	36.7
71 F Hare Rate 3-10 88.3 88.0 This-Beam Transition 3-10 12.4 23.4 Standard (31) 3-10 3-13 4.5 Standard (31) Standard (31) Standard (31) Standard (31) Standard (31) Standard (31) Standard (3		1/2 Post Spacing	Simulation	27.8	43.1
17.1 Flare Reito 3-11 2.3 2.4 2.14 13.1 2.14 2.14 2.14 13.1 2.14 2.14 2.14 13.1 2.14 2.14 2.14 14.1 4.33 6.51 15.2 11.1 3.11 2.14 2.14 15.2 11.1 4.33 6.51 15.2 11.1 11.1 4.33 6.51 15.2 11.1 11.1 11.1 11.1 11.1 15.2 11.1 11.1 11.1 11.1 11.1 15.2 11.1 11.1 11.1 11.1 11.1 11.1 15.2 11.1		7:1 Flare Rate	3-10	36.3	38.0
The deam Transition 3-10 12.4 2.14 2.14 Standard (31 m) 3-11 2.14 2.14 2.14 Standard (31 m) 3-10 3-13 6.14 10.14 System performed 3-10 3-10 10.14		7:1 Flare Rate	3-11	75.8	87.9
Image: Book State		Thrie-Beam Transition	3-10	12.4	23.4
Image: Additional of the state of the s	and a second	Thrie-Beam Transition	3-11	21.4	21.4
Note: 12 - 61 - 61 - 61 - 61 - 61 - 61 - 61 -		Rep Stondard (21 in)	ort 350 Update Pro	oposed Vehicle	S EO 4
Image: State of the second		Standard (31 In.)	3-11	43.9	59.4
Image: State of the Midwest Guardrall System with a system through the system with the system of the system with the system wit	10	52 III. Height	3-10	51.5	45.1
Image: Additional and the second of the s			1	Eull cor	le such testing of
NCHP 550 6'-5'' Stendard MSS Guardrall System in NCLHR Report 350 cest designation. NCHR 550 6'-5'' Stendard MSS Guardrall Complex test designation. It is grant to be addressed on the base of the		No. 18 Sec.		Full-sca	ale crash testing of
Stein Wilder Stein Status Stein Status St		100 Star Star Star	2	the Mic	iwest Guardrail
https://www.commercedings.com/ https://wwww.commercedings.com/ https://wwwwwwwwwwwwwwwwwwwww		Partie Ca		System	with asymmetrica
System performed successfully under NCHR Report 350 test designa- tions 3-10 and 3-11.		A STAR CONTRACTOR	The state of the	🔚 thrie-b	eam transition.
NCHRP 350 This Beam 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 12'-6" 10' Gauge 12'-6" 12'-6				System	performed
Report 350 test designs tion 3-10 and 3-11.	ACCOUNTS AND ACCOUNTS			success	fully under NCHR
NOHRP 350 Complete Transition 12 Coupe 12 Coupe 13 Coupe 13 Coupe 13 Coupe 13 Coupe 14 Coupe 15 Coupe 1				Report	350 test designa-
And 3-11. and 3-1. and	NCHPD 350 6'-3"				tions 3-10
Stendard MCS Cuardrail Section We been We bee	Compliant Transition 10 Gauge				and 3-11.
Image: Section Weight of Secting Section Weight of Se	6'-3" Asymmetrical W-beam 1: 12 Gauge to Thrie Beam 12	2'-6"	Standard	MGS Guard	rail
Wist 250° tong post Wist 250° tong post Wist 250° tong post Wist 250° tong post <th>Thrie Beam Section W-</th> <th>-beam</th> <th></th> <th></th> <th></th>	Thrie Beam Section W-	-beam			
Image: Strategy of the strategy					
Wissing				_	<u> </u>
Wisx12x90* long posts Wisx9x72* long posts Wisx12x90* long posts Wisx12x90* long posts Image: Wisx12x90* long posts Wisx12x90* long posts Image: Wisx12x90* long posts Image: Wisx12x90* long posts			TT T		
West2x90* long potts West2x* long potts West2x90* specing West2x* long potts West2x* long potts West2x* long potts Understand Vest2x90* long potts Vest2x90* long Vest2x* long potts Understand Vest2x* long potts Vest2x90* long Vest2x* long potts Vest2x90* long Vest2x* long potts Vest2x90* long Vest2x* long Vest2x90* long Vest2x* Vest2x90* long Vest2x* Vest2x90* long Vest2x90* Vest2x90* Vest2x90* <th></th> <th></th> <th></th> <th>i i</th> <th></th>				i i	
Windowsky with a state of the state of					
Wext 12:y0* sporting Wext 22:y0* sport 22:y0* sporting Wext 22:y0* sporting </th <th></th> <th></th> <th></th> <th></th> <th></th>					
W6x12x90* long posts W6x9x7* long posts W6x9x7* specing W6x9x7* long posts W6x9x7* specing W6x9x7* long posts W6x9x7* long posts Understand W6x9x7* long posts Understand W6x9x1 Understand W6x1 Unders				1	
W6x92x9 "spacing W6x92x9 "spacing W6x92x9 "spacing Understand Understand Understand W6x92x9 "spacing Understand Understand Understand W6x92x9 "spacing Understand Understand Understand W6x92x9 "spacing Understand W1x92x9 "spacing Understand W1x92x9 "spacing Understand W1x92x9 "spacing W1x92x9 W			U	1	
Weit 12:290* end gosts Weit 97:2* long posts Weit 2:290* specing Weit 97:2* long posts Image: Construction of the specing of the spe				!	
 Wight 12 kg0° long posts Wight 22 kg0° long					
<complex-block>Wey2rge broken Wey2rge broke</complex-block>		\setminus			
 By By B	W6u12u00" long parts				
 I/4 Post Spacing Long Span Design for the Midwest Guardrail System – 25' nonnested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 	@ 37.5" spacing @	37.5" spacing			
 I/4 Post Spacing Long Span Design for the Midwest Guardrail System – 25' non-nested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of a 2:1 Slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 					
 I/4 Post Spacing Long Span Design for the Midwest Guardrail System – 25' non- nested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 	, 	/ _	•		
 Long Span Design for the Midwest Guardrail System – 25' non- nested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 	I/4 Post Spacin	ון הן סו <mark>ו</mark> ו	ngoing	g MGS	S lesting
 Consider the widewest of the wide			l ong Shan	Decian f	or the Midwest
 Guardran System – 25 hon- nested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 			Cuardrail C	Designi	
 Mesca mested system for crossing shallow culverts. MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 		and the second second	Guardran S	system –	25 non-
 shallow culverts. MGS on Breakpoint of a 2:1 Slope Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 	NPG-6		nested syst	tem for ci	rossing
 MGS on Breakpoint of a 2:1 Slope – Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 		1	shallow cul	verts.	
 Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 			MGS on Br	eaknoint	of a 2.1 Slope
 Posts located on breakpoint of slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 			Dooto loo	otod on L	rockpoint of
 Slope. Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 		-			леакропттог
 Approach Slopes for W-Beam Guardrail Systems – MGS located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 			siope.		
Guardrail Systems – MGS located 5' from travelway on an 8:1 slope.		•	Approach S	Slopes fo	r W-Beam
 South an Oystem 3 - MOO located 5' from travelway on an 8:1 slope. MGS utilizing small-diameter Southern Yellow Pine, Ponderosa 	NPG-6		Guardrail 9	vstems -	-MGS located
MGS utilizing small-diameter Southern Yellow Pine, Ponderosa		Chine and	E' from troy		
MGS utilizing small-diameter Southern Yellow Pine, Ponderosa			5 nom trav	erway of	ran o. i siope.
Southern Yellow Pine, Ponderosa		•	MGS utilizi	ng small-	diameter
Yellow Pine, Ponderosa			Southern		
Ponderosa		ATTITUDE OF	Yellow Pine	-	Contraction of the local division of the loc
			Ponderosa	- ,	

Full-scale crash testing of the Midwest Guardrail System with 1/4 post spacing (18.75 in.). The system performed successfully and was also approved for both 1/4 and 1/2 post spacing (37.5 in.).

Questions and Answers

Temporary Concrete Barrier Deflection Limits for Reduced Speeds

State Question:

What is your opinion of reducing the deflection spacing behind a temporary barrier if the speed limit is marked at lower speeds than the test speed of 62 mph? Right now we are following the criteria from your group in the deflection recommendation report of 45 in. unless used on roadways with 10 ft lanes or greater, in which case we reduce the deflection to 24 in.

MwRSF Response:

The original Iowa F-shape temporary concrete barrier was crash tested to the TL-3 criteria of NCHRP Report No. 350. In that test, dynamic barrier deflections of approximately 45 in. were observed. Later, MwRSF published a report which stated that when the barrier is positioned near a bridge deck edge using the freestanding configuration, the clear distance between the deck edge and back-side barrier base should be 45.3 in. However, for all other applications, the design deflection limit should be set at 24 in. This distance corresponds to the distance that the lowa temporary barrier could be expected to deflect under the 85th percentile impact for passenger cars and light trucks. The 85th percentile impact condition was determined to be a 3/4-ton pickup truck impacting at a speed of 36 mph at 27.1 degrees.



Recent Reports

- TRP-03-80-98 Crash Testing of South Dakota's Cable Guardrail System for Median Applications
- TRP-03-83-99 Guardrail and Guardrail Terminals Installed Over Curbs
- TRP-03-88-99 Development of a 7.62-m Long Span Guardrail System—Phase II
- TRP-03-99-00 Development of a W-Beam Guardrail System for Use on a 2:1 Slope
- TRP-03-119-03 Development of Standards for Placement of Steel Guardrail Posts in Rock
- TRP-03-127-03 Bridge Rails and Transition for Pedestrian Protection
- TRP-03-154-04 Dynamic Testing of Wooden Guardrail Posts—White and Red Pine Species Equivalency Study
- TRP-03-155-05 Evaluation of Alternative Cable Anchor Designs and Three-Cable Guardrail Adjacent to Steep Slope
- TRP-03-126-03 Embankment Widening and Slopes Required for Gating-Type End Terminals

*Check out the publications section of Midwest Roadside Safety Facility website to request copies of the reports

Ongoing Research

- Development of a Guardrail Treatment at Intersecting Roadways – Short radius guardrail system.
- Evaluation of Rigid Hazards in Zone of Intrusion – Rigid poles mounted on top of and behind rigid barriers.
- Three-Cable Guardrail In Front of Slope – Will utilize a 48" offset from a 1.5:1 slope and a 4' post spacing.
- Development of a Four-Strand, High-Performance Cable Barrier – Tensioned, non-proprietary system to be tested in a depressed median.
- Evaluation of Transverse Culvert Safety Grate – Full-scale test of 20'x20' culvert grate on 3:1 slope.
- New TL-5 Median Barrier and Anchor – Concrete median barrier.

Cost Effective Measures for Roadside Design on Low Volume Roads.

 Termination of Temporary Concrete Barrier – Develop anchorage and run L.O.N. test.



Zone of Intrusion Study

- Develop Temporary Concrete Barrier Transition – Transition to permanent and/or other longitudinal barrier.
- Evaluation of the Safety Performance of Vertical and Safety Shaped Concrete Barriers.

MIDWEST ROADSIDE SAFETY FACILITY UNIVERSITY OF NEBRASKA-LINCOLN E527 NEBRASKA HALL LINCOLN, NE 68588-0529 (402) 472-0965 www.mwrsf.unl.edu

